



PRINTABLE RING SIZE GUIDE

IMPORTANT

Before you print this document, check your print dialog box to make sure that you have NOT checked "scale to fit page" or "shrink to fit page". You should print this document as "Actual size" or "100%". To check if this is printed accurately, check that the lines to the right measures 50 mm or 2 inches.



If You don't know your ring size, we recommend using some of the following options:

1. Measure by matching your ring size over the circles below:

- Select a ring that properly fits the intended finger.
- Make sure your ring is round, and has not lost it's shape.
- Place the ring over the circles, starting with the smaller size.
- Move up in size until the circle completely fills the inside of the ring without overlapping, and you can no longer see any white around the edge..
- If the ring falls between two sizes, choose the larger size.
- Keep in mind that a wide ring, more than 5 mm, usually requires a larger size

Ring size = Inside circumference in mm

46

Ø 14,65 mm

48

Ø 15,29 mm

50

Ø 15,92 mm

52

Ø 16,56 mm

54

Ø 17,2 mm

56

Ø 17,83 mm

58

Ø 18,47 mm

60

Ø 19,1 mm

62


Ø 19,75 mm

64

Ø 20,37 mm

2. Measure by using a ruler.

- Select a ring that fits the finger you intend to wear your ring on.
- Make sure your ring is round, and has not lost it's shape.
- Measure the inside diameter of your ring in millimeters (mm) using a ruler.
- The measured total number of millimeters multiplied by 3,14 is your ring size.



3. Measure by visiting a jeweler.

A ring should fit comfortably on the finger of the wearer as well as it should be tight enough to prevent it from accidentally falling off. The best and most accurate way to measure a ring size is by visiting a local jeweler. Jewelers use a set of graduated rings and other specialized tools to determine ring sizes. Make sure to tell them whether the sizing is for a skinny or a wider ring.

INTERNATIONAL RING SIZE CONVERSION

US	UK	EU	DE	BR	JP	CH
3	F 1/2	44.0	14.00	7	4	4.0
3 1/4	G	44.5	14.25	8	5	5.0
3 1/2	G 1/2	45.5	14.50	9		5.5
3 3/4	H	46.0	14.75		6	6.0
4	H 1/2	46.5	15.00	10	7	7.0
4 1/4	I	47.0				7.5
4 1/2	J	48.0	15.25	11	8	8.0
4 3/4	J 1/2	48.5	15.50	12		9.0
5	K	49.0	15.75	13	9	9.5
5 1/4	K 1/2	50.0			10	10.0
5 1/2	L	50.5	16.00	14		10.5
5 3/4	L 1/2	51.0	16.25		11	11.5
6	M	51.5	16.50	15		12.0
6 1/4	M 1/2	52.5	16.75	16	12	12.5
6 1/2	N	53.0	17.00		13	13.5
6 3/4	N 1/2	53.5		17		14.0
7	O	54.5	17.25		14	14.5
7 1/4	O 1/2	55.0	17.50	18		15.0
7 1/2	P	55.5	17.75	19	15	16.0
7 3/4	P 1/2	56.5	18.00		16	16.5
8	Q	57.0	18.25	20		17.0
8 1/4	Q 1/2	57.5			17	18.0
8 1/2	R	58.0	18.50	21		18.5
8 3/4	R 1/2	59.0	18.75	22	18	19.0
9	S	59.5	19.00		19	20.0
9 1/4	S 1/2	60.0	19.25	23		20.5
9 1/2	T	61.0	19.50	24	20	21.0
9 3/4	T 1/2	61.5	19.75			21.5
10	U	62.0	20.00	25	21	22.5
10 1/4	U 1/2	63.0			22	23.0
10 1/2	V	63.5	20.25	26		23.5
10 3/4	V 1/2	64.0	20.50	27	23	24.5
11	W	64.5	20.75		24	25.0
11 1/4	W 1/2	65.5		28		25.5
11 1/2	X	66.0	21.00		25	26.0
11 3/4	X 1/2	66.5	21.25	29	26	27.0
12	Y	67.5	21.50	30		27.5
12 1/4	Y 1/2	68.0	21.75		27	28.0
12 1/2	Z	68.5	22.00	31	28	29.0
12 3/4	Z 1/2	69.0				29.5
13	Z+1	70.0	22.25	32	29	30.0
13 1/4	Z+1 1/2	70.5	22.50	33		31.0
13 1/2	Z+2	71.0		34	30	32.0
13 3/4	Z+2 1/2	71.5	22.75	35		32.5
14	Z+3	72.0	23.00		31	33.0
14 1/4	Z+3 1/2	72.5	23.25	35	32	33.5
14 1/2	Z+4	73.5	23.50			34.5
14 3/4	Z+4 1/2	74.0		36	33	35.0
15	Z+5	74.5	23.75	37		36.0
15 1/4	Z+5 1/2	75.0	24.00		34	36.5
15 1/2	Z+6	76.0	24.25	38		37.0
15 3/4	Z+6 1/2	76.5	24.50		35	37.5
16	Z+7	77.0		39		38.5